

SOOT BLOWERS

Air Systems Soot Blowers are available in various models for travel up to 7.6 meters distance for cleaning any type of heating surface. The retractable, rotary & wall deslagger type of soot blowers are built for reliable operation both indoors & outdoors and also in all weather conditions, specifically for low maintenance, reliability, versatility and maximum cleaning performance.

We manufacture top quality line of soot blowers suitable for Boilers, air heaters & furnace applications Our range of soot blowers includes:-

- Retractable Soot Blower
- Wall Deslagger
- Rotary Soot Blowers

Rotary Soot Blowers are suitable for cleaning convection surfaces of boiler tubes, economizers or tubular reheaters of packaged industrial or field erected boilers.









SPECIFICATIONS OF RETRACTABLE SOOT BLOWERS

Rotary Speed 4 to 12 rpm
Maximum Cleaning Radius- 0.5 to 4m
Maximum Lance Length 7600mm

Blowing Medium Steam or Compressed Air

Purge Angle 0-360o

Media Consumption 30 – 100 kg/min Nozzle Dia 19-31.75mm

Effective Radius Purge 2m

Air System manufacture excellent quality of lances, feed tubes & swivel tube assemblies for any make & model of soot blowers. Our feed tubes are made of the highest quality materials and are ground finished to ensure a long working life. All welding joints of soot blower parts are done with state of the art TIG equipment.

We also offer precision machined SBV Head or Poppet valve assemblies which run through a series of tests, including hydrostatic pressure checks to ensure an absolutely leak proof valve.





AIR SYSTEMS LIMITED

61/32, TTK Road Chennai - 600 018, India Tel.: +91 44 24660888 Fax: +91 44 24988499

Fax: +91 44 24988499 Email: nka@asplparts.com

www.asplparts.com